


NAIL & COPPER TAG FIXED IN CONCRETE SURFACE
PLAN (TYPE 'C')

24" X 2" MIN. I.D. GALVANIZED IRON PIPE (SUBDIVISION BOUNDARY MONUMENT TYPE 'A')

* FOR SECTION AND QUARTER SECTION CORNERS THAT FALL IN ROADWAY SEE STD. DWG. NO. 300B

24" X 3/4" MIN. I.D. GALVANIZED IRON PIPE (LOT & PARCEL CORNER MONUMENT TYPE 'B')

COPPER TAG STAMPED WITH R.E. OR L.S. NUMBER OR STAMPED PLASTIC PLUG (SEE DETAIL BELOW RIGHT)



SECTION (TYPE 'B' ALTERNATIVE)
PLASTIC PLUG

SECTION A-A

NOTES:

1. SUBDIVISION BOUNDARY MONUMENT TYPE 'A' TO BE SET 6" BELOW FINISH SUB-GRADE IN ROADWAY OR FLUSH AT TRACT BOUNDARY CORNERS.
2. ALL LOT AND PARCEL CORNERS SHALL USE TYPE 'B' MONUMENTS SET AT PROPER GRADE WITH A COPPER DISC OR PLASTIC PLUG BEARING THE REGISTERED CIVIL ENGINEER OR LAND SURVEYOR NUMBER.
3. TYPE 'C' MONUMENT TO CONSIST OF LEAD PLUG OR STEEL PIN WITH COPPER IDENTIFICATION DISC SET IN CONCRETE CURB OR WALL. (SEE DETAIL ABOVE RIGHT.)

DATE: SEPT. 2001

Signature on File
CITY ENGINEER

TYPE A, B, & C MONUMENTS

DEPARTMENT OF PUBLIC WORKS CITY OF PALM DESERT

SCALE: NONE

STD DRAWING NO.
300A